

ATP Industrial Grade CompactFlash Card

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



ATP Industrial Grade CompactFlash Card has enhanced endurance levels for extended product life cycle by utilizing selected SLC NAND flash and Advanced Wear Leveling technology. Moreover, the implemented AutoRefresh technology monitors the error bit levels during each read operation to better ensure data integrity.

Key Features

- SLC (Single-Level-Cell) NAND Flash with a longer lifespan
- Enhanced endurance with Advanced Wear Leveling algorithm
- Bad Block Management
- Read Disturb Protector AutoRefresh to ensure data integrity during read operation
- Built-in hardware-based data protection technology during power failure -PowerProtector
- Supports S.M.A.R.T. ATA feature set

Applications

- Portable compution
- Automation
- Industrial PC
- Gaming
- On board data storage



Specifications

Product Name	CompactFlash Card		
Flash Type	SLC	MLC*	
Density	512MB to 32GB	8GB to 32GB	
Performance	Sequential Read up to 61 MB/s	Sequential Read up to 110 MB/s	
	Sequential Write up to 55 MB/s	Sequential Write up to 46 MB/s	
Interface	UDMA 0~7		
Operation Temperature	-40°C to 85°C	0°C to 70°C	
Reliability	Advanced Wear Leveling & Bad Block Management		
	TBW** (max.): 640 TB	TBW** (max.): 38.4 TB	
	MTBF @25°C: >5,000,000 hours		
	Number of Insertions: 10,000 minimum		
Dimensions: LxWxH (mm)	36.4 x 42.8 x 3.3		

^{*} Available on a project basis.

Ordering Information

Density	SLC	MLC*
512MB	AF512CFI-OEM	-
1GB	AF1GCFI-OEM	-
2GB	AF2GCFI-OEM	-
4GB	AF4GCFI-OEM	-
8GB	AF8GCFI-OEM	AF8GCFP3-OEM
16GB	AF16GCFI-OEM	AF16GCFP7-OEM
32GB	AF32GCFI-OEM	AF32GCFP7-OEM

^{*} Available on a project basis.

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368 FAX: +886-2-2659-4982 sales-apac@atpinc.com ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com ATP JAPAN

TEL: +81-3-6206-8097 FAX: +81-3-6206-8098 sales-japan@atpinc.com ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-5080-2219 sales@cn.atpinc.com



^{**} All TBW data listed are under highest random write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.